Machine foot HXGT150-10-8



ARTICLE NUMBER 1015279

Type HXGT/HXGT AS

The design and patent protected solid HXGT and HXGT AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

The HXGT and HXGT AS consist of a separated footplate and spindle connected by the diametrically centered elevation on the footplate.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The HXGT AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	No	
Drawing no.	NGI 165817	
Footplate diameter	150 mm	5.91"
Height adjustment	203.20 mm	8.00"
Height max.	202 mm	7.95"
Height min.	66 mm	2.60"
Height total	224 mm	8.82"
Mounting holes	0 Pieces	
Nom. load	77500 N	
Nom. pull	0 N	
Spindle length	203.20 mm	8.00"
Thread diameter	10 mm	0.39"
Thread length	203.20 mm	8.00"
Thread size	UNC 1-8	
Thread standard	UNC	

Technical specifications

