Machine foot HXGT-AS150-24-150



ARTICLE NUMBER 1015314

Type HXGT/HXGT AS

The design and patent protected solid HXGT and HXGT AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

The HXGT and HXGT AS consist of a separated footplate and spindle connected by the diametrically centered elevation on the footplate.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The HXGT AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165879	
Footplate diameter	150 mm	5.91"
Height adjustment	150 mm	5.91"
Height max.	157 mm	6.18"
Height min.	67 mm	2.64"
Height total	176 mm	6.93"
Mounting holes	0 Pieces	
Nom. load	69200 N	
Nom. pull	0 N	
Rubber type	S75	
Spindle length	150 mm	5.91"
Thread diameter	24 mm	0.94"
Thread length	150 mm	5.91"
Thread size	M24	
Thread standard	Metric C	

Technical specifications

