# Machine foot HXG105-36-100



ARTICLE NUMBER 1011430

## Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

| Technical specifications | | |
|---|---|---|
| Antislip | No | |
| Drawing no. | NGI 058424 | |
| Footplate diameter | 104 mm | 4.09” |
| Height adjustment | 106 mm | 4.17” |
| Height max. | 98 mm | 3.86” |
| Height min. | 73 mm | 2.87” |
| Height total | 127 mm | 5.00” |
| Mounting holes | 0 Pieces | |
| Net weight | 1545 g | |
| Nom. load | 110000 N | 24728.98lbs |
| Nom. pull | 20000 N | 4496.18lbs |
| Spindle length | 106 mm | 4.17” |
| Thread diameter | 36 mm | 1.42” |
| Thread length | 106 mm | 4.17” |
| Thread size | M36 | |
| Thread size | M36 | |
| Thread standard | Metric C | |

## Technical specifications

