Machine foot HX125-M20-230, AISI 304, Black NBR



ARTICLE NUMBER 1003828

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067287	
Footplate diameter	125 mm	4.92”
Height adjustment	185 mm	7.28”
Height max.	245 mm	9.65”
Height min.	60 mm	2.36”
Height total	261 mm	10.28”
Mounting holes	0 Pieces	
Net weight	1051 g	
Nom. load	32000 N	7193.89lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	Sh75A	
Spindle length	221 mm	8.70”
Thread diameter	20 mm	0.79”
Thread length	223 mm	8.78”
Thread size	M20	
Thread standard	Metric C	

Technical specifications

