Machine foot HX125-58-12



ARTICLE NUMBER 1003868

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067340	
Footplate diameter	125 mm	4.92"
Height adjustment	304.80 mm	12.00"
Height max.	331 mm	13.03"
Height min.	74 mm	2.91"
Height total	345 mm	13.58"
Mounting holes	0 Pieces	
Net weight	983 g	
Nom. load	7600 N	1708.55lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	S75	
Spindle length	304.80 mm	12.00"
Thread diameter	58 mm	2.28"
Thread length	304.80 mm	12.00"
Thread size	UNC 5/8	
Thread standard	UNC	

Technical specifications

