Machine foot HX-FIX066-12-10, 1 fixation



ARTICLE NUMBER 1003953

Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067648	
Footplate diameter	65 mm	2.56"
Height adjustment	254 mm	10.00"
Height max.	277 mm	10.91"
Height min.	65 mm	2.56"
Height total	288 mm	11.34"
Mounting holes	1 Pieces	
Net weight	390 g	
Nom. load	4100 N	921.72lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	S75	
Spindle length	254 mm	10.00"
Thread diameter	12 mm	0.47"
Thread length	254 mm	10.00"
Thread size	UNC 1/2	
Thread standard	UNC	

Technical specifications

