Machine foot HX-FIX106-34-12, 1 fixation



ARTICLE NUMBER 1004136

Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067809	
Footplate diameter	105 mm	4.13”
Height adjustment	304.80 mm	12.00”
Height max.	327 mm	12.87”
Height min.	76 mm	2.99”
Height total	344 mm	13.54”
Mounting holes	1 Pieces	
Net weight	1025 g	
Nom. load	16000 N	3596.94lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	S75	
Spindle length	304.80 mm	12.00”
Thread diameter	34 mm	1.34”
Thread length	304.80 mm	12.00”
Thread size	UNC 3/4	
Thread standard	UNC	

Technical specifications

