
# Machine foot HX125-M30-150, AISI 304, Blue NBR



ARTICLE NUMBER 1018262

## Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 201596 | |
| Footplate diameter | 125 mm | 4.92” |
| Height adjustment | 139 mm | 5.47” |
| Mounting holes | 0 Pieces | |
| Net weight | 1227 g | |
| Nom. load | 32000 N | 7193.89lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | Sh75A | |
| Spindle length | 146 mm | 5.75” |
| Thread diameter | 30 mm | 1.18” |
| Thread length | 139 mm | 5.47” |
| Thread size | M30 | |
| Thread size | M30 | |
| Thread standard | Metric C | |

## Technical specifications

