Machine foot HX066-16-150, Blue rubber



ARTICLE NUMBER 1018711

Type H

The design and patent protected H, H Fixing & H Double Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments. H61 Fixing fully-threaded levelling foot is the optimal choice for low-weight machinery and equipment in diverse production environments.

Lowered cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The H Fixing, H Double Fixing, H61 Fixing is designed to be fastened to the floor by the two stainless steel-embedded rubber fixing plates. Bolts, nuts and washers can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 221549	
Footplate diameter	65 mm	2.56”
Height adjustment	106 mm	4.17”
Height max.	160 mm	6.30”
Height min.	54 mm	2.13”
Height total	173 mm	6.81”
Mounting holes	1 Pieces	
Nom. load	9000 N	2023.28lbs
Rubber type	B75	
Spindle length	139 mm	5.47”
Thread length	139 mm	5.47”
Thread size	M16	
Thread standard	Metric C	

Technical specifications

