Machine foot HX080-M24-230, AISI 304, Blue NBR



ARTICLE NUMBER 1018801

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.


Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 222677	
Footplate diameter	80 mm	3.15”
Height adjustment	182 mm	7.17”
Height max.	241 mm	9.49”
Height min.	59 mm	2.32”
Height total	260 mm	10.24”
Mounting holes	0 Pieces	
Net weight	916 g	
Nom. load	15000 N	3372.13lbs
Rubber type	Sh75A	
Spindle length	221 mm	8.70”
Thread size	M24	
Thread size	M24	
Thread standard	Metric C	

Technical specifications



NGI A/S Virkelyst 5 9400 Nørresundby Denmark +45 98 17 45 00 ngi@ngi.dk