# Machine foot HX-FIX126-M20-100, AISI 304, Blue NBR



ARTICLE NUMBER 1018902

## Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 222840 | |
| Footplate diameter | 125 mm | 4.92" |
| Height adjustment | 61 mm | 2.40" |
| Height max. | 121 mm | 4.76" |
| Height min. | 60 mm | 2.36" |
| Height total | 137 mm | 5.39" |
| Mounting holes | 1 Pieces | |
| Nom. load | 32000 N | 7193.89lbs |
| Rubber type | SH75A | |
| Spindle length | 97 mm | 3.82" |
| Thread size | M20 | |
| Thread size | M20 | |
| Thread standard | Metric C | |

## Technical specifications

