
Machine foot HX150-M12-100, AISI 304, Blue NBR



ARTICLE NUMBER 1018916

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.


Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 222523	
Footplate diameter	150 mm	5.91"
Height adjustment	67 mm	2.64"
Height max.	129 mm	5.08"
Height min.	62 mm	2.44"
Height total	139 mm	5.47"
Mounting holes	0 Pieces	
Net weight	1016 g	
Nom. load	70000 N	15736.63lbs
Rubber type	Sh75A	
Spindle length	97 mm	3.82"
Thread size	M12	
Thread size	M12	
Thread standard	Metric C	

Technical specifications



NGI A/S Virkelyst 5 9400 Nørresundby Denmark +45 98 17 45 00 ngi@ngi.dk