# Machine foot HX080-M20-180, AISI 304, Black NBR



ARTICLE NUMBER 1002370

## Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 067140 | |
| Footplate diameter | 80 mm | 3.15” |
| Height adjustment | 136 mm | 5.35” |
| Height max. | 195 mm | 7.68” |
| Height min. | 59 mm | 2.32” |
| Height total | 211 mm | 8.31” |
| Mounting holes | 0 Pieces | |
| Net weight | 603 g | |
| Rubber type | Sh75A | |
| Spindle length | 172 mm | 6.77” |
| Thread length | 172 mm | 6.77” |
| Thread size | M20 | |
| Thread standard | Metric C | |

## Technical specifications

