Machine foot HX080-58-4



ARTICLE NUMBER 1002413

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067174	
Footplate diameter	80 mm	3.15"
Height adjustment	101.60 mm	4.00"
Height max.	126 mm	4.96"
Height min.	73 mm	2.87"
Height total	141 mm	5.55"
Mounting holes	0 Pieces	
Net weight	369 g	
Nom. load	15000 N	3372.13lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	S75	
Spindle length	101.60 mm	4.00"
Thread diameter	58 mm	2.28"
Thread length	101.60 mm	4.00"
Thread size	UNC 5/8	
Thread standard	UNC	

Technical specifications

