# Machine foot HX105-M20-180, AISI 304, Black NBR



ARTICLE NUMBER 1003754

## Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 067213 | |
| Footplate diameter | 105 mm | 4.13” |
| Height adjustment | 118 mm | 4.65” |
| Height max. | 195 mm | 7.68” |
| Height min. | 77 mm | 3.03” |
| Height total | 212 mm | 8.35” |
| Mounting holes | 0 Pieces | |
| Net weight | 779 g | |
| Nom. load | 22000 N | 4945.80lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | Sh75A | |
| Spindle length | 172 mm | 6.77” |
| Thread diameter | 20 mm | 0.79” |
| Thread length | 172 mm | 6.77” |
| Thread size | M20 | |
| Thread standard | Metric C | |

## Technical specifications

