Machine foot HX105-M24-70, AISI 304, Black NBR



ARTICLE NUMBER 1003763

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067216	
Footplate diameter	105 mm	4.13”
Height adjustment	33 mm	1.30”
Height max.	93 mm	3.66”
Height min.	60 mm	2.36”
Height total	112 mm	4.41”
Mounting holes	0 Pieces	
Net weight	634 g	
Nom. load	22000 N	4945.80lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	Sh75A	
Spindle length	72 mm	2.83”
Thread diameter	24 mm	0.94”
Thread length	70 mm	2.76”
Thread size	M24	
Thread standard	Metric C	

Technical specifications

