Machine foot HX105-54-10



ARTICLE NUMBER 1003788

Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 067268	
Footplate diameter	105 mm	4.13"
Height adjustment	254 mm	10.00"
Height max.	260 mm	10.24"
Height min.	81 mm	3.19"
Height total	288 mm	11.34"
Mounting holes	0 Pieces	
Net weight	1781 g	
Nom. load	22000 N	4945.80lbs
Nom. pull	4000 N	899.24lbs
Nom. pull	4000 N	899.24lbs
Rubber type	S75	
Spindle length	254 mm	10.00"
Thread diameter	54 mm	2.13"
Thread length	254 mm	10.00"
Thread size	UNC 1 1/4	
Thread standard	UNC	

Technical specifications

