# Machine foot HX-FIX126-10-10, 1 fixation



ARTICLE NUMBER 1014518

## Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 157763 | |
| Footplate diameter | 125 mm | 4.92” |
| Height adjustment | 254 mm | 10.00” |
| Height max. | 271 mm | 10.67” |
| Height min. | 85 mm | 3.35” |
| Height total | 294 mm | 11.57” |
| Mounting holes | 1 Pieces | |
| Nom. load | 32000 N | 7193.89lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | S75 | |
| Spindle length | 254 mm | 10.00” |
| Thread diameter | 10 mm | 0.39” |
| Thread length | 254 mm | 10.00” |
| Thread size | UNC 1-8 | |
| Thread standard | UNC | |

## Technical specifications

