# Machine foot HX-FIX126-10-12, 1 fixation



ARTICLE NUMBER 1014519

## Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 157765 | |
| Footplate diameter | 125 mm | 4.92" |
| Height adjustment | 304.80 mm | 12.00" |
| Height max. | 322 mm | 12.68" |
| Height min. | 85 mm | 3.35" |
| Height total | 345 mm | 13.58" |
| Mounting holes | 1 Pieces | |
| Nom. load | 32000 N | 7193.89lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | S75 | |
| Spindle length | 304.80 mm | 12.00" |
| Thread diameter | 10 mm | 0.39" |
| Thread length | 304.80 mm | 12.00" |
| Thread size | UNC 1-8 | |
| Thread standard | UNC | |

## Technical specifications

