Machine foot HX-FIX126-M12-230, AISI 304, Black NBR



ARTICLE NUMBER 1014529

Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 157650	
Footplate diameter	125 mm	4.92"
Height adjustment	191 mm	7.52"
Height max.	251 mm	9.88"
Height min.	60 mm	2.36"
Height total	261 mm	10.28"
Mounting holes	1 Pieces	
Nom. load	4200 N	944.20lbs
Nom. pull	4000 N	899.24lbs
Rubber type	SH75A	
Spindle length	221 mm	8.70"
Thread diameter	12 mm	0.47"
Thread length	223 mm	8.78"
Thread size	M12	
Thread size	M12	
Thread standard	Metric C	

Technical specifications

