Machine foot HX-FIX126-M16-150, AISI 304, Black NBR



ARTICLE NUMBER 1014538

Type HX

The design and patent protected HX & HX Fixing fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 157658	
Footplate diameter	125 mm	4.92”
Height adjustment	106 mm	4.17”
Height max.	166 mm	6.54”
Height min.	60 mm	2.36”
Height total	179 mm	7.05”
Mounting holes	1 Pieces	
Nom. load	30800 N	6924.12lbs
Nom. pull	4000 N	899.24lbs
Rubber type	SH75A	
Spindle length	139 mm	5.47”
Thread diameter	16 mm	0.63”
Thread length	139 mm	5.47”
Thread size	M16	
Thread size	M16	
Thread standard	Metric C	

Technical specifications

