# Machine foot HX105-78-6



ARTICLE NUMBER 1016805

## Type HX

The design and patent protected HX fully-threaded levelling foot is the optimal choice for machinery and equipment in diverse production environments.

Minimum cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The HX Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 193162 | |
| Footplate diameter | 105 mm | 4.13” |
| Height adjustment | 152.40 mm | 6.00” |
| Height max. | 172 mm | 6.77” |
| Height min. | 82 mm | 3.23” |
| Height total | 192 mm | 7.56” |
| Mounting holes | 0 Pieces | |
| Nom. load | 22000 N | 4945.80lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | S75 | |
| Spindle length | 152.40 mm | 6.00” |
| Thread diameter | 78 mm | 3.07” |
| Thread length | 152.40 mm | 6.00” |
| Thread size | UNC 7/8 | |
| Thread standard | UNC | |

## Technical specifications

