Machine foot XHJ105-XHJG5883-RHOX5832, Blue rubber



ARTICLE NUMBER 1017979

Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 198617	
Footplate diameter	105 mm	4.13"
Height adjustment	66 mm	2.60"
Height max.	197 mm	7.76"
Height min.	131 mm	5.16"
Height total	235 mm	9.25"
Mounting holes	2 Pieces	
Net weight	1418 g	
Nom. load	24100 N	5417.90lbs
Nom. pull	20000 N	4496.18lbs
Rubber type	B75	
Sleeve diameter	58 mm	2.28"
Sleeve length	32 mm	1.26"
Spindle length	210 mm	8.27"
Thread diameter	58 mm	2.28"
Thread length	115 mm	4.53"
Thread size	UNC 5/8	
Thread size	UNC 5/8	
Thread standard	UNC	

Technical specifications

