Machine foot XH-FIX66-M20 x 280-M20, AISI 304, Black NBR, 1 fi-xation



ARTICLE NUMBER 1018249

Type XH

The design and patent protected XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Technical specifications		
Material	AISI 304	
Thread size	M20	
Thread standard	Metric C	
Footplate diameter	66	
Rubber Type	Black NBR	
Net weight	1186 g	
Total adjustment	99 mm	3.90"
Height total	308 mm	12.13"
Max. adjustment	270 mm	10.63"
Min. adjustment	171 mm	6.73"
Nom. load	9000 N	2023.28lbs
Nom. pull	4000 N	899.24lbs
Mounting holes	1 Pieces	

Technical specifications





