XH065-XH12150-RHOX1250, blue rubber



ARTICLE NUMBER 1018350

Type XH

The design and patent protected XH & XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Certified hygienic levelling feet are always delivered with hygienic nuts.

Technical specifications

	XH	
Antislip	Yes	
Drawing no.	NGI 202509	
Footplate diameter	65 mm	2.56"
Height adjustment	36 mm	1.42"
Height max.	140 mm	5.51"
Height min.	104 mm	4.09"
Height total	178 mm	7.01"
Mounting holes	0 Pieces	
Nom. load	9000 N	
Nom. pull	4000 N	
Rubber type	S75	
Sleeve diameter	16 mm	0.63"
Sleeve length	50 mm	1.97"
SleeveType	RHOX	
Spindle length	150 mm	5.91"
Thread diameter	16 mm	0.63"
Thread length	85 mm	3.35"
Thread size	M12	
Thread standard	Metric C	

Technical specifications

