Machine foot XH-FIX126-M20 x 280/150-M20 x 115, AISI 304, Blue NBR, 1 fixation



ARTICLE NUMBER 1026477

Type XH

The design and patent protected XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Technical specifications		
Material	AISI 304	
Thread size	M20	
Thread standard	Metric C	
Footplate diameter	126	
Rubber Type	Blue NBR	
Net weight	1604 g	
Total adjustment	101 mm	3.98"
Height total	314 mm	12.36"
Max. adjustment	276 mm	10.87"
Min. adjustment	175 mm	6.89"
Nom. load	22000 N	4945.80lbs
Nom. pull	4000 N	899.24lbs
Mounting holes	1 Pieces	

Technical specifications

