# Machine foot XH125-UNC 5/8 x 5.90/3,3-UNC 5/8 x 2, AISI 304, Black NBR



ARTICLE NUMBER 1000165

## Type XH

The design and patent protected XH levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

## Technical specifications

| | XH | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 066216 | |
| Footplate diameter | 125 mm | 4.92" |
| Height adjustment | 36 mm | 1.42" |
| Height max. | 146 mm | 5.75" |
| Height min. | 110 mm | 4.33" |
| Height total | 184 mm | 7.24" |
| Mounting holes | 0 Pieces | |
| Net weight | 903 g | |
| Nom. load | 30300 N | 6811.71lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | SH75A | |
| Sleeve diameter | 58 mm | 2.28" |
| Sleeve length | 50 mm | 1.97" |
| SleeveType | RHOX | |
| Spindle length | 150 mm | 5.91" |
| Thread length | 85 mm | 3.35" |
| Thread size | UNC 5/8 | |
| Thread standard | UNC | |

## Technical specifications

