# Machine foot XH-FIX81-UNC 1 1/4 x 5.90/3,5-UNC 1 1/4 x 2, AISI 304, Black NBR, 1 fixation



ARTICLE NUMBER 1000217

## Type XH

The design and patent protected XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

## Technical specifications

| | XH | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 066363 | |
| Footplate diameter | 81 mm | 3.19" |
| Height adjustment | 36 mm | 1.42" |
| Height max. | 145 mm | 5.71" |
| Height min. | 109 mm | 4.29" |
| Height total | 183 mm | 7.20" |
| Mounting holes | 1 Pieces | |
| Net weight | 1327 g | |
| Nom. load | 15000 N | 3372.13lbs |
| Nom. pull | 4000 N | 899.24lbs |
| Rubber type | SH75A | |
| Sleeve diameter | 54 mm | 2.13" |
| Sleeve length | 50 mm | 1.97" |
| SleeveType | RHOX | |
| Spindle length | 150 mm | 5.91" |
| Thread length | 88 mm | 3.46" |
| Thread size | UNC 1 1/4 | |
| Thread standard | UNC | |

## Technical specifications

