Machine foot XHJ105-UNC 1 x 8.30/4.50-UNC 1 x 3.10, AISI 304, Black NBR, 2 fixations



ARTICLE NUMBER 1000356

Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

Technical specifications		
Antislip	Yes	
Rubber type	SH75A	
Thread size	UNC 1	
Thread standard	UNC	
Drawing no.	NGI 066627	
Net weight	1896 g	
Height total	235 mm	9.25”
Thread length	115 mm	4.53”
Footplate diameter	105 mm	4.13”
Sleeve diameter	10 mm	0.39”
Sleeve length	80 mm	3.15”
Height max.	197 mm	7.76”
Height min.	131 mm	5.16”
Height adjustment	66 mm	2.60”
Spindle length	210 mm	8.27”
Nom. load	77500 N	17422.69lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications



