Machine foot XH-FIX106-XH20280-RHOX20115, Black NBR, Sleeve outer Ø 39,5



ARTICLE NUMBER 1014665

Type XH

The design and patent protected XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Technical specifications

	XH	
Antislip	Yes	
Compression load	22000 N	4945.80lbs
Drawing no.	NGI 122211	
Footplate diameter	105 mm	4.13”
Height adjustment	99 mm	3.90”
Height max.	273.80 mm	10.78”
Height min.	174.70 mm	6.88”
Height total	313.80 mm	12.35”
Mounting holes	1 Pieces	
Net weight	1939 g	
Nom. load	22000 N	4945.80lbs
Nom. pull	4000 N	899.24lbs
Rubber type	SH75A	
Sleeve diameter	20 mm	0.79”
Sleeve length	115 mm	4.53”
SleeveType	RHOX	
Spindle length	280 mm	11.02”
Thread diameter	20 mm	0.79”
Thread length	115 mm	4.53”
Thread size	M20	
Thread standard	Metric C	

Technical specifications





