Machine foot XHJ150-M20 x 150/85-M20 x 50, AISI 304, Black NBR, 2 fixations



ARTICLE NUMBER 1014841

Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

Technical specifications		
Antislip	Yes	
Rubber type	SH75A	
Thread size	M20	
Thread standard	Metric C	
Footplate diameter	150	
Drawing no.	NGI 163779	
Net weight	2122 g	
Height total	175 mm	6.89”
Thread length	85 mm	3.35”
Sleeve diameter	20 mm	0.79”
Sleeve length	50 mm	1.97”
Height max.	137 mm	5.39”
Height min.	101 mm	3.98”
Height adjustment	36 mm	1.42”
Spindle length	150 mm	5.91”
Nom. load	48200 N	10835.79lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications

