# Machine foot XHJ150-M20 x 210/115-M20 x 80, AISI 304, Black NBR, 2 fixations



ARTICLE NUMBER 1014842

## Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Rubber type | SH75A | |
| Thread size | M20 | |
| Thread standard | Metric C | |
| Footplate diameter | 150 | |
| Drawing no. | NGI 163809 | |
| Net weight | 2355 g | |
| Height total | 235 mm | 9.25” |
| Thread length | 115 mm | 4.53” |
| Sleeve diameter | 20 mm | 0.79” |
| Sleeve length | 80 mm | 3.15” |
| Height max. | 197 mm | 7.76” |
| Height min. | 131 mm | 5.16” |
| Height adjustment | 66 mm | 2.60” |
| Spindle length | 210 mm | 8.27” |
| Nom. load | 48200 N | 10835.79lbs |
| Nom. pull | 20000 N | 4496.18lbs |
| Mounting holes | 2 Pieces | |

## Technical specifications

