Machine foot XHJ080-XHJG30150-RHOX3050, 2 fixations



ARTICLE NUMBER 1014867

Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 163787	
Footplate diameter	80 mm	3.15"
Height adjustment	33 mm	1.30"
Height max.	134 mm	5.28"
Height min.	101 mm	3.98"
Height total	175 mm	6.89"
Mounting holes	2 Pieces	
Nom. load	110000 N	
Nom. pull	20000 N	
Rubber type	S75	
Sleeve diameter	30 mm	1.18"
Sleeve length	50 mm	1.97"
Spindle length	150 mm	5.91"
Thread diameter	30 mm	1.18"
Thread length	88 mm	3.46"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

