# Machine foot XHG080-XHJG36150-RHOX3650



ARTICLE NUMBER 1014924

## Type XHG + XHJ

The design and patent protected XHG+XHJ is the optimal choice for machinery and equipment that has to comply with the strictest hygieneic requirements.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

XHJ can be fastened to the floor. Certified hygienic levelling feet are always delivered with hygienic nuts.

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 164324 | |
| Footplate diameter | 80 mm | 3.15" |
| Height adjustment | 33 mm | 1.30" |
| Height max. | 134 mm | 5.28" |
| Height min. | 101 mm | 3.98" |
| Height total | 175 mm | 6.89" |
| Mounting holes | 0 Pieces | |
| Nom. load | 110000 N | |
| Nom. pull | 20000 N | |
| Rubber type | S75 | |
| Sleeve diameter | 36 mm | 1.42" |
| Sleeve length | 50 mm | 1.97" |
| Spindle length | 150 mm | 5.91" |
| Thread diameter | 36 mm | 1.42" |
| Thread length | 88 mm | 3.46" |
| Thread size | M36 | |
| Thread standard | Metric C | |

## Technical specifications

