Machine foot XH080-XH3459-RHOX3420, Blue NBR



ARTICLE NUMBER 1017689

Type XH

The design and patent protected XH levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.


All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.


Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

Technical specifications

	XH	
Antislip	Yes	
Drawing no.	NGI 197658	
Footplate diameter	80 mm	3.15"
Height adjustment	35 mm	1.38"
Height max.	145 mm	5.71"
Height min.	110 mm	4.33"
Height total	183 mm	7.20"
Net weight	693 g	
Nom. pull	4000 N	899.24lbs
Rubber type	SH75A	
Sleeve diameter	34 mm	1.34"
Sleeve length	20 mm	0.79"
SleeveType	RHOX	
Thread diameter	34 mm	1.34"
Thread length	85 mm	3.35"
Thread size	UNC 3/4	
Thread standard	UNC	

Technical specifications





NGI A/S Virkelyst 5 9400 Nørresundby Denmark +45 98 17 45 00 ngi@ngi.dk