# Machine foot XH080-XH5459-RHOX5420, Blue rubber



ARTICLE NUMBER 1017690

## Type XH

The design and patent protected XH & XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Certified hygienic levelling feet are always delivered with hygienic nuts.

## Technical specifications

| | XH | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 197654 | |
| Footplate diameter | 80 mm | 3.15" |
| Height adjustment | 36 mm | 1.42" |
| Height max. | 145 mm | 5.71" |
| Height min. | 109 mm | 4.29" |
| Height total | 183 mm | 7.20" |
| Mounting holes | 0 Pieces | |
| Nom. load | 15000 N | |
| Nom. pull | 4000 N | |
| Rubber type | B75 | |
| Sleeve diameter | 54 mm | 2.13" |
| Sleeve length | 42 mm | 1.65" |
| SleeveType | RHOX | |
| Spindle length | 150 mm | 5.91" |
| Thread diameter | 54 mm | 2.13" |
| Thread length | 85 mm | 3.35" |
| Thread size | UNC 1 1/4-7 | |
| Thread standard | UNC | |

## Technical specifications

