Machine foot XH-FIX081-XH30210-RHOX3080, 1



ARTICLE NUMBER 1017720

Type XH

The design and patent protected XH & XH Fixing levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The XH Fixing is designed to be fastened to the floor by the fixing plate.

Certified hygienic levelling feet are always delivered with hygienic nuts. However, UNC levelling feet are delivered with hygienic washers untill autumn 2019 after which these will also be delivered with hygienic nuts.

Technical specifications

	XH	
Antislip	Yes	
Drawing no.	NGI 197542	
Footplate diameter	80 mm	3.15"
Height adjustment	66 mm	2.60"
Height max.	202 mm	7.95"
Height min.	139 mm	5.47"
Height total	243 mm	9.57"
Mounting holes	1 Pieces	
Nom. load	15000 N	
Nom. pull	4000 N	
Rubber type	B75	
Sleeve diameter	30 mm	1.18"
Sleeve length	80 mm	3.15"
SleeveType	RHOX	
Spindle length	210 mm	8.27"
Thread diameter	30 mm	1.18"
Thread length	115 mm	4.53"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

