Machine foot XH80-M20 x 210/115-M20 x 80, AISI 304, Black NBR



ARTICLE NUMBER 1000099

Type XH

The design and patent protected XH levelling foot is the optimal choice for machinery and equipment that has to comply with the strictest hygienic requirements.

The thread is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as a counter nut.

All movable parts are 100% hygienically sealed even if the load on the foot is removed. All sealings are blue and therefore detectable by scanning systems.

Minimum cleaning effort is obtained by the design of the self-draining surfaces. Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

Technical specifications

	XH	
Antislip	Yes	
Drawing no.	NGI 066174	
Footplate diameter	80 mm	3.15"
Height adjustment	66 mm	2.60"
Height max.	205 mm	8.07"
Height min.	139 mm	5.47"
Height total	243 mm	9.57"
Mounting holes	0 Pieces	
Net weight	946 g	
Nom. load	15000 N	3372.13lbs
Nom. pull	4000 N	899.24lbs
Rubber type	SH75A	
Sleeve diameter	20 mm	0.79"
Sleeve length	80 mm	3.15"
SleeveType	RHOX	
Spindle length	210 mm	8.27"
Thread length	115 mm	4.53"
Thread size	M20	
Thread standard	Metric C	

Technical specifications

