
Nut NLXH UNC 1-8, AISI 316, Blue NBR



ARTICLE NUMBER 8000077

Certified hygienic NLXH nuts with blue sealing are the right choice of nuts to be used on all machinery in all certified hygienic wash-down environments. The sealing blocks out water and bacteria and prevents a non-hygienic metal-to-metal assembly. Round-headed and self-draining surfaces with a maximal roughness of 0.8 µm Ra. The design of the nuts does not deviate from the sizes of current standard nuts. Therefore, wrench sizes, thread heights etc. all remains the same making it very easy to upgrade and replace standard nuts. NGI's certified hygienic nuts are used for floor-mounting of certified hygienic levelling feet to ensure compliance with current legislation towards hygienic design. The NLXH is used when the length of exposed bolt thread is adapted to the nut's B2 measurement.

- Certified in accordance with 3-A (RPSCQC)
- Certified in accordance with EHEDG hygienic standard TYPE EL - CLASS I AUX
- Minimizes cleaning time and water consumption
- Surfaces with a maximal roughness of 0,8 µm Ra
- Available in sizes M5-M24

Technical specifications

Bolt lenght	10 mm	0.39"
Country of origin	DK	
Drawing no.	NGI 194746	
Flat width	38.10 mm	1.50"
Head height	23 mm	0.91"
Max tightening torque	572 Nm	
Net weight	193 g	
Outer diameter	52.88 mm	2.08"
Sealing material	Blue NBR	
Thread length	14 mm	0.55"
Thread size	UNC 1-8	
Thread standard	UNC	

Technical specifications

